

Inch Tapered Roller Bearing

Bearing No.	Boundary dimensions [mm]						Basic load ratings (kN)		
	d	B	R	D	C	r	T	Dynamic (Cr)	Static (Cor)
LM501349/314/Q	41,275	73,431	21,430	63	68	7,65	7500	10000	0,35
11162/11300/Q	41,275	76,200	18,009	52	56	6,1	7000	9500	0,34
11163/11300/Q	41,275	76,200	18,009	52	56	6,1	7000	9500	0,34
24780/24720/Q	41,275	76,200	22,225	68,2	86,5	9,65	6700	9500	0,43
M802048/011/QCL7C	41,275	82,550	26,543	85	91,5	10,6	6700	9000	0,62
3585/3525/Q	41,275	87,312	30,162	102	132	15	6000	8500	0,85
HM803146/110/Q	41,275	88,900	30,162	108	127	14,6	6000	8000	0,90
HM803146/2/110/2/QCL7C	41,275	88,900	30,162	108	127	14,6	6000	8000	0,90
526/522/Q	41,275	101,600	34,925	151	190	22,8	5000	7500	1,45
25577/2/25520/2/Q	42,875	82,931	23,812	80,9	106	12	6000	9000	0,57
25577/2/25523/2/Q	42,875	83,058	23,876	80,9	106	12	6000	9000	0,57
25580/25523/Q	44,450	82,931	26,988	80,9	106	11,8	6000	9000	0,57
25580/25522/Q	44,450	83,058	23,876	80,9	106	11,8	6000	9000	0,57
HM803149/110/Q	44,450	88,900	30,162	108	127	14,6	6000	8000	1,50
HM803149/2/110/2/QCL7C	44,450	88,900	30,162	108	127	14,6	6000	8000	1,50
HM903249/2/210/2/Q	44,450	92,250	30,958	116	122	14	5300	7000	1,00
HM903249/W/210/QCL7C	44,450	92,250	30,958	116	122	14	5300	7000	1,00
53178/53377/Q	44,450	95,250	30,958	88	96,5	11,4	5000	7000	0,93
HM807040/010/QCL7C	44,450	104,775	36,512	170	204	22,4	5000	6700	1,50
535/532A	44,450	107,950	38,100	151	190	22,8	4800	7000	1,85
535/532X	44,450	107,950	38,100	151	190	22,8	4800	7000	1,70
3586/3525/Q	45,237	87,313	30,162	102	132	15	6000	8500	0,85
LM102949/910/Q	45,242	73,431	19,558	62	75	8,15	7000	9500	0,30
LM603049/011/Q	45,242	77,788	19,842	62	69,5	7,65	7000	9000	0,37
25590/25520/Q	45,618	82,931	23,812	80,9	106	11,8	6000	9000	0,55
25590/25523/Q	45,618	82,931	26,988	80,9	106	11,8	6000	9000	0,55
25590/25522/Q	45,618	83,058	23,876	80,9	106	11,8	6000	9000	0,55
359S/354X/Q	46,038	85	20,638	81,5	81,5	9,3	6700	8500	0,49
369S/2/362A/2/Q	47,625	88,900	23,812	76,5	91,5	10,4	5600	8000	0,55
HM804846/2/810/2/Q	47,625	95,250	30,162	108	146	17,3	5000	7500	0,95